



US 20100317879A1

(19) **United States**

(12) **Patent Application Publication**
Zhao et al.

(10) **Pub. No.: US 2010/0317879 A1**

(43) **Pub. Date: Dec. 16, 2010**

(54) **METHODS FOR CONVERSION OF CARBOHYDRATES IN IONIC LIQUIDS TO VALUE-ADDED CHEMICALS**

(75) Inventors: **Haibo Zhao**, The Woodlands, TX (US); **Johnathan E. Holladay**, Kennewick, WA (US); **Zongchao C. Zhang**, Norwood, NJ (US)

Correspondence Address:
BATTELLE MEMORIAL INSTITUTE
ATTN: IP SERVICES, K1-53
P. O. BOX 999
RICHLAND, WA 99352 (US)

(73) Assignee: **BATTELLE MEMORIAL INSTITUTE**, Richland, WA (US)

(21) Appl. No.: **12/862,649**

(22) Filed: **Aug. 24, 2010**

Related U.S. Application Data

(62) Division of application No. 11/774,036, filed on Jul. 6, 2007.

(60) Provisional application No. 60/836,188, filed on Aug. 7, 2006, provisional application No. 60/851,545, filed on Oct. 13, 2006, provisional application No. 60/938,988, filed on May 18, 2007.


Publication Classification

(51) **Int. Cl.**
C07D 307/50 (2006.01)

(52) **U.S. Cl.** **549/489**

(57) **ABSTRACT**

Methods are described for converting carbohydrates including, e.g., monosaccharides, disaccharides, and polysaccharides in ionic liquids to value-added chemicals including furans, useful as chemical intermediates and/or feedstocks. Fructose is converted to 5-hydroxymethylfurfural (HMF) in the presence of metal halide and acid catalysts. Glucose is effectively converted to HMF in the presence of chromium chloride catalysts. Yields of up to about 70% are achieved with low levels of impurities such as levulinic acid.







Fig. 1
(Prior Art)



cat=numerous MCl_x ; Acids

Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8

METHODS FOR CONVERSION OF CARBOHYDRATES IN IONIC LIQUIDS TO VALUE-ADDED CHEMICALS

CROSS REFERENCE TO RELATED APPLICATION

[0001] This application claims priority from and is a divisional of U.S. patent application Ser. No. 11/774,036 filed Jul. 6, 2007, which in turn claims priority from Provisional application 60/836,188 filed Aug. 7, 2006; Provisional application 60/851,545 filed Oct. 13, 2006; and Provisional application 60/938,988 filed May 18, 2007 incorporated herein their entirety.

[0002] This invention was made with Government support under Contract DE-AC05-76RLO1830 awarded by the U.S. Department of Energy. The Government has certain rights in the invention.

FIELD OF THE INVENTION

[0003] The present invention relates to methods for conversion of carbohydrates in ionic liquids to value-added chemicals at substantial yields.

BACKGROUND OF THE INVENTION

[0004] Replacing petroleum feedstocks with biomass feedstocks will require efficient methods for converting carbohydrates to a diverse number of chemical compounds. A major barrier to achieving this goal is a current inability to effectively utilize 5-carbon (C5) and 6-carbon (C6) carbohydrate building blocks derived from nature as potential feedstocks, including such abundant sugars as, e.g., glucose and fructose. 5-Hydroxymethylfurfural (HMF), an important versatile sugar derivative, is also considered a key intermediate between petroleum-based industrial organic chemistry and bio-based carbohydrate chemistry [Werpy et al. in "Top Value Added Chemicals from Biomass" United States Department of Energy report number DOE/GO-102004-1992; and Kamm et al. "Lignocellulose-based Chemical Products and Product Family Trees" in "Biorefineries-Industrial Processes and Products", 133 pp, Vol. 2 Edited by Kamm, B., Gruber, P. R. & Kamm, M, WILEY-VCH Verlag GmbH & Co. KGaA, Weinheim, 2006]. For example, HMF and its derivatives can potentially replace petroleum-based building blocks [Bicker et al. in *Green Chem.* 5, 280-284 (2003)] used to make plastics and fine chemicals. However, processes that produce pure HMF from abundant renewable carbohydrates as a basis for biorefinery platforms based on utilization of HMF must produce high yields and have low energy costs. For example, while HMF has been proposed as a key intermediate to produce liquid alkanes from renewable biomass resources [Leshkov et al., *Science* 312, 1933-1937 (2006)], high production costs currently limit availability and use of HMF industrially. Further, processes that produce HMF involve use of acid catalysts and are essentially limited to fructose as a feed material [Asghari et al., *Ind. Eng. Chem. Res.* 45, 2163-2173 (2006); Kuster et al, *STARCH-STARKE* 42, 314-321 (1990); Leshkov et al., *Science* 312, 1933-1937 (2006); Tyrlik et al., *Carbohydr. Res.* 315, 268-272 (1999)]. FIG. 1 illustrates a conventional process for acid-catalyzed conversion of carbohydrates. In the figure, conversion of 6-carbon sugars employs concentrated acid (e.g., sulfuric acid) as a catalyst. Acids are corrosive, however, and have drawbacks including product contamination, and difficult

recycling and waste disposal issues. Acids further catalyze side reactions leading to byproducts that require complicated product separations for product purification that increase costs. For example, in water under acidic conditions, HMF decomposes to levulinic acid and formic acid, making purification of HMF difficult. Challenges obtaining high yields of dehydration products from conversion of fructose are described, e.g., by Carlini et al. [*Applied Catalysis A: General* 275 (2004) 111-118].

[0005] When glucose is the feed material, HMF yields are usually low [Tyrlik et al., *Carbohydr. Res.* 315, 268-272 (1999); Watanabe et al., *Carbohydr. Res.* 340, 1925-1930 (2005)]. Under normal processing conditions, glucose fails to convert to HMF at high yields. Generally, glucose is poorly converted, presumably a consequence of competing reaction pathways that lead to formation of byproducts. With fructose, HMF yield is reported to increase in systems which partition HMF from H₂O. For example, HMF yields increase in strong polar organic solvents such as dimethylsulfoxide (DMSO) as part of an aqueous-organic reaction medium [Leshkov et al., *Science* 312, 1933-1937 (2006)]. In another solvent system, HMF is reported to be formed from fructose in an ionic liquid solvent consisting of [BMIM]PF₆ or [BMIM]PF₄ with added co-solvent (e.g., DMSO) further including AMBERLYST-15®, an acidic polymer, as catalyst [Lansalot-Matras et al., *Catal. Commun.* 4, 517-520 (2003)]. In the absence of DMSO co-solvent, best yield of HMF is reported to be 40% to 52%. [Lansalot-Matras et al., *Catal. Commun.* 4, 517-520 (2003); and Moreau et al., *J. Mol. Catal. A: Chem.* 253, 165-169 (2006)]. In another system, a specialized ionic liquid, [HMIM]Cl is reported to act as a proton-transfer agent, or acid catalyst [Moreau et al., *J. Mol. Catal. A: Chem.* 253, 165-169 (2006)].

[0006] Polysaccharides (e.g., cellulose) are another class of carbohydrates that are a rich source of carbohydrate building blocks with both high conversion and high yield potential. However, polysaccharides typically require pretreatment to depolymerize the carbohydrates and provide necessary building blocks for conversion. Cellulose, for example, is presently pretreated with acid and subsequently converted to glucose via enzymatic hydrolysis. However, enzyme costs are high and complexity of processing leads to high capital costs. Alternatives such as acid hydrolysis produce by-products which are metabolic poisons to biological fermentation organisms, eliminating fermentation as a route to product conversion. Consequently, while carbohydrates can be converted through various processes including hydrolysis and biological fermentation, poisoning, slow processing, high production costs, and difficult separations result in high processing costs.

[0007] Accordingly, there remains a need for new processes that provide conversion of carbohydrates to value-added chemicals and chemical feedstock products at high conversion, high selectivity, and high yields.

SUMMARY OF THE INVENTION

[0008] The invention relates to the use of ionic liquids for selective conversion of carbohydrates to value-added chemicals. In one method of the invention, selective conversion of a carbohydrate to value-added chemical(s) includes the steps of: mixing the carbohydrate up to a limit of solubility with an ionic liquid; heating the carbohydrate in the ionic liquid at a reaction temperature in the absence of added catalyst for a

reaction time sufficient for conversion of the carbohydrate. Conversion of the carbohydrate produces furans at substantial yield.

[0009] In various embodiments, preferred ionic liquids used as solvents for conversion of carbohydrates have a chemical formula: 1-R₁-3-R₂-imidazolium chloride ([R₁R₂IM]Cl), where R₁ and R₂ are alkyl groups of formula (C_xH_{2x+1}) where X=1 to 18. In another embodiment, ionic liquids include a cation of chemical formula 1-R₁-3-R₂-imidazolium, where R₁ and R₂ are alkyl groups of formula (C_xH_{2x+1}) where X=1 to 18, and an anion. Anions include, but are not limited to, e.g., halides, sulfates, sulfonates, phosphates, acetates, phosphates, triflates, hexafluorophosphates, tetrafluoroborates, hexafluoroborates, and aluminum chloride. In another embodiment, the anion is methanesulfonate or trifluoromethanesulfonate. In other embodiments, an ionic liquid is 1-ethyl-3-methyl-imidazolium chloride ([EMIM]Cl) or 1-butyl-3-methyl-imidazolium chloride ([BMIM]Cl).

[0010] In other embodiments, ionic liquids selected for use include pyridinium salts (e.g., N-alkylpyridinium salts), phosphonium salts (e.g., P,P,P,P-tetraalkylphosphonium salts), and tetraalkylammonium salts (e.g., N,N,N,N-tetraalkylammonium salts) that include a stoichiometric quantity of a suitable anion, described herein.

[0011] In yet other embodiments, carbohydrates including, e.g., monosaccharides (e.g., glucose, fructose, mannose, and galactose, and derivatives thereof, e.g., sorbitol, anhydrosorbitol), disaccharides (e.g., sucrose, maltose, lactose, cellobiose, and derivatives thereof), and polysaccharides (e.g., maltodextrins, starches, cellulose, and derivatives thereof) are converted in the absence of a co-solvent to value-added chemicals including, e.g., furfurals, e.g., 5-hydroxymethylfurfural (HMF).

[0012] In still yet other embodiments, 5-carbon sugars (e.g., arabinose, xylose, ribose, and lyxose) are converted to value-added chemicals including, e.g., furfural.

[0013] In yet other embodiments, 6-carbon sugars (e.g., glucose, fructose, mannose, and galactose) are converted to value-added chemicals, including, e.g., 5-hydroxymethylfurfurals.

[0014] In other embodiments, a furan obtained from conversion of fructose by the process of the invention includes 5-hydroxymethylfurfural (HMF). In another embodiment, a furan is obtained in the absence of a catalyst.

[0015] In other embodiments, fructose is converted to HMF in conjunction with a catalyst that is an acid. In other embodiments, fructose is converted to HMF with a catalyst that is a metal halide. Metal halides include, but are not limited to, e.g., AlCl₃, CrCl₂, CrCl₃, FeCl₂, FeCl₃, CuCl, CuBr, CuCl₂, CuBr₂, VCl₃, MoCl₃, PdCl₂, PtCl₂, PtCl₄, RuCl₃, RhCl₃, and combinations thereof.

[0016] Reaction times for conversion of carbohydrates vary, e.g., from about 0.01 minutes to about 300 minutes; or from about 0.01 minutes to about 30 minutes; or from about 0.01 minutes to about 5 minutes. Reaction temperatures for conversion of carbohydrates vary from about 20° C. to about 400° C.; or from about 80° C. to about 250° C.; or from about 100° C. to about 200° C.

[0017] In one embodiment, fructose is converted to HMF at a reaction temperature of about 80° C. and a reaction time of between about 1 hour and about 4 hours.

[0018] In still yet another embodiment, fructose is converted to HMF at a reaction temperature of about 120° C. and a reaction time of about 180 minutes. In another embodiment,

reaction time and reaction temperature is between about 1 hour and about 3 hours at about 120° C.

[0019] In yet another embodiment, fructose is converted to HMF in 1-ethyl-3-methylimidazolium [EMIM]CH₃SO₃ to which methane sulfonate or its conjugate acid are added as a catalyst. Reaction temperature and reaction time are between about 80° C. for about 2 hours and about 30° C. for about 12 hours.

[0020] In another embodiment, conversion of fructose gives a yield of levulinic acid and α-angelicalactone below about 1 percent by weight and more particularly below about 0.1 percent by weight.

[0021] In one embodiment, conversion of glucose to HMF proceeds at a reaction temperature of about 100° C. and a reaction time of about 3 hours.

[0022] In yet another embodiment, conversion of glucose produces a furan that is furfural.

[0023] In another embodiment, the carbohydrate converted is a sugar alcohol yielding a furan that is an anhydrosugar alcohol or a dianhydrosugar alcohol. In another embodiment, the sugar alcohol is sorbitol.

[0024] In another embodiment, conversion of carbohydrates is achieved in a batch reactor or a batch reactor system. In other embodiments, conversion of carbohydrates is achieved in a continuous flow reactor or a continuous flow reactor system.

[0025] In still yet other embodiments, reaction times and reaction temperatures for conversion of carbohydrates are from about 0.01 minutes at about 400° C. to about 10 h at about 20° C. Conversion of carbohydrates can also be achieved at reaction times of less than or equal to about 0.01 minutes, e.g., in conjunction with a flash conversion process.

[0026] In yet other embodiments, conversion of carbohydrates includes a reaction time of from about 0.01 minutes to about 5 hours and a reaction time of from about 400° C. down to about 20° C.

[0027] In another embodiment, conversion of glucose to HMF includes a reaction time of from about 0.01 minutes to about 5 hours and a reaction time of from about 400° C. down to about 20° C.

[0028] In still yet another embodiment, conversion of carbohydrates is effected in a reaction time of about 0.01 minutes, e.g., in conjunction with a flash conversion process.

[0029] In yet another embodiment, carbohydrates are converted in a reaction time and a reaction temperature of between about 0.01 minutes at about 250° C. and about 12 hours at about 20° C.

[0030] In various embodiments, conversion of carbohydrates is greater than or equal to about 80 percent and yield of furans is greater than or equal to about 50 percent on a mole basis; or at least about 35 percent by weight.

[0031] In another embodiment, conversion of glucose gives yields of levulinic acid and α-angelicalactone of less than about 3 percent by weight.

[0032] A more complete appreciation of the invention will be readily obtained by reference to the following description of the accompanying drawings in which like numerals in different figures represent the same structures or elements.

BRIEF DESCRIPTION OF THE DRAWINGS

[0033] FIG. 1 (Prior Art) illustrates a process for conversion of carbohydrates to HMF by conventional acid catalyzed dehydration.

[0034] FIG. 2 illustrates a reaction process for conversion of fructose to HMF in an exemplary ionic liquid, with added metal halide catalysts to promote desired chemistry, according to embodiments of the process of the invention.

[0035] FIG. 3 illustrates a reaction process for conversion of glucose to HMF in an exemplary ionic liquid, with added CrCl_2 metal halide catalyst to promote desired chemistry, according to another embodiment of the process of the invention.

[0036] FIG. 4 is a plot comparing conversion results for fructose and glucose to HMF as a function of temperature, according to different embodiments of the process of the invention.

[0037] FIG. 5 is a plot showing conversion results for fructose in an exemplary ionic liquid treated with various metal halide catalysts, according to different embodiments of the process of the invention.


[0038] FIG. 6 is a plot showing conversion results for glucose in an exemplary ionic liquid treated with various metal halide catalysts, according to different embodiments of the process of the invention.

[0039] FIG. 7 is a plot showing conversion results for glucose as a function of time in an exemplary ionic liquid treated with CrCl_2 , CuCl_2 , and FeCl_2 metal halide catalysts.

[0040] FIG. 8 is a plot presenting conversion results for glucose in an exemplary ionic liquid treated with CrCl_2 metal halide catalyst, according to a preferred embodiment of the process of the invention.

DETAILED DESCRIPTION OF THE INVENTION


[0041] The term “Imidazoles” as used herein refers to the class of heterocyclic aromatic compounds of general structural formula [A]:



[A]

where R represents functional groups as will be understood by those of skill in the chemical art.

[0042] The term “Imidazole” [CAS No. 288-32-4] [Mol. Wt.: 68.08] as used herein refers to the chemical compound of chemical formula ($\text{C}_3\text{H}_4\text{N}_2$) having general structural formula [B]:



[B]


[0043] The term “Imidazolium” as used herein refers to the cationic portion of ion-forming salts from the imidazole class of organic compounds, having general structural formula [C]:




[C]

where R_1 and R_2 are alkyl groups of formula ($\text{C}_x\text{H}_{2x+1}$) where $\text{X}=1$ to 18.

[0044] The terms “Furans” and “a Furan” as used herein refer to compounds from the class of heterocyclic organic compounds having general structural formula [D1] and [D2]:




[D1]




[D2]

where R_1 , R_2 , R_3 , and R_4 are functional groups including, e.g., H or C; C may further include O and/or H, defining, e.g., aldehyde or alcohol functional groups. “Furan” [CAS Number 110-00-9] ($\text{C}_4\text{H}_4\text{O}$) is included in this class of compounds having structural formula [01], where R_1 and R_2 are H.

[0045] The term “Sugar Alcohols” as used herein refers to compounds of chemical formula [$\text{C}_n\text{H}_{2n+2}\text{O}_n$] where $n=1, 2, 3$, etc. General structural formulas for representative 5-carbon and 6-carbon sugar alcohols are illustrated in [E1] and [E2]:




[E1]




[E2]

[0046] The term “Anhydro sugar alcohols” as used herein refers to compounds having general structural formula [F1] and [F2]:




[F1]



[F2]

[0047] The term “Dianhydrosugar alcohols” as used herein refers to compounds having general structural formula [G]:



[G]

[0048] While preceding compounds have been illustrated using generalized structures, no limitation to specific stereoisomers is implied.

[0049] Abbreviation nomenclature used herein to denote ionic liquids identifies the cationic portion of the ionic liquid, e.g., 1-ethyl-3-methyl-imidazolium, by bracket, e.g., [EMIM] or [EMIM]⁺. The anionic portion of the ionic liquid, e.g., chloride (Cl or Cl⁻) is identified by placement outside the bracket (e.g., [EMIM]Cl or [EMIM]⁺Cl⁻). Unless otherwise noted, nomenclature for ionic liquids with or without ionic charges are used interchangeably, e.g., [EMIM]⁺Cl⁻ or [EMIM]Cl.

[0050] The term “triflates” has reference to chemical compounds that include a trifluoromethanesulfonate functional group (CF₃SO₃⁻) or a corresponding acid conjugate (CF₃SO₃H).

[0051] The term “Selectivity” as used herein is defined by equation [1]:

$$\text{Selectivity} = \left(\frac{\text{Moles Product Formed}}{\text{Moles Starting Material Reacted}} \right) \quad [1]$$

[0052] The term “Conversion” as used herein is defined by equation [2]:

$$\text{Conversion} = 1 - \left(\frac{\text{Moles Unreacted Starting Material}}{\text{Moles Starting Material}} \right) \quad [2]$$

[0053] The term “Yield” as used herein is defined by equation [3]:

$$\text{Yield} = \left(\frac{\text{Moles Product Formed}}{\text{Moles Starting Material}} \right) \quad [3]$$

Ionic Liquids

[0054] Ionic liquids (IL) suitable for use as solvents in conjunction with the invention provide solubility to the carbohydrates selected for conversion therein. Properties of the ionic liquid solvents vary according to the cationic, alkyl, and anionic group constituents of the liquids. Preferred ionic liquids include salts of the 1-R₁-3-R₂-imidazolium class of compounds, where R₁ and R₂ are alkyl groups of formula (C_xH_{2x+1}) where X=1 to 18, further including a stoichiometric quantity of a selected anion. In these ionic liquids, the cationic portion (or cation) of the ionic liquid includes a 5-member imidazolium ring and alkyl groups R₁ and R₂. The anionic

portion (or anion) of the ionic liquid can vary. Anions include, but are not limited to, e.g., halides including, e.g., chloride (Cl⁻), bromide (Br⁻), and iodide (I⁻); halogen-free anions, including, e.g., sulfates, sulfonates (e.g., alkyl sulfonates), phosphates, acetates, and triflates (e.g., alkyl triflates); hexafluorophosphates (PF₆⁻); tetrafluoroborates (BF₄⁻); hexafluoroborates (BF₆⁻); and aluminum chloride (AlCl₄⁻). Other ionic liquids suitable for use include pyridinium salts (e.g., N-alkylpyridinium salts), phosphonium salts (e.g., P,P,P-tetraalkylphosphonium salts), and tetralkylammonium salts (e.g., N,N,N,N-tetraalkylammonium salts) that include a stoichiometric quantity of a suitable anion, described herein.

[0055] Ionic liquids can contain impurities that are catalytic. In an illustrative example, reactivity of a carbohydrate in an “as-received” [EMIM]CH₃SO₃ ionic liquid had high activity due to presence of contaminants and/or impurities in the ionic liquid. However, when the “as-received” ionic liquid was purified to remove contaminants and/or impurities, reactivity of the carbohydrate was negligible. In general, at low reaction temperatures, catalysts are required for conversion of carbohydrates in ionic liquids.

[0056] Conversion of fructose to HMF is demonstrated using three exemplary [AMIM]Cl ionic liquid solvent systems, where A is an alkyl group, including, but not limited to, e.g., ethyl, butyl, octyl, and the like. Corresponding ionic liquids are: 1-ethyl-3-methylimidazolium [EMIM]Cl; 1-butyl-3-methylimidazolium chloride [BMIM]Cl; and 1-octyl-3-methylimidazolium chloride [OMIM]Cl, but is not limited thereto. These ionic liquids are preferred ionic liquid (IL) solvent systems for conversion of carbohydrates to versatile chemicals at high yields, including, e.g., 5-hydroxymethylfurfural (HMF).

[0057] In one process, according to an embodiment of the invention, fructose is converted in the presence of metal halide catalysts to HMF at high yields. In another process, fructose is converted to HMF at selected reaction temperatures in the absence of any added catalyst. In another process, fructose is converted in the presence of a mineral acid to HMF at high yields.

Conversion of 6-Carbon Sugars

[0058] Conversion of 6-C sugars (e.g., glucose and fructose) to HMF in ionic liquids has been demonstrated.

[0059] FIG. 2 illustrates a reaction process for conversion of fructose to HMF in an exemplary ionic liquid, [EMIM]Cl, with metal halide catalysts or acid catalysts added to promote desired chemistry. While the furanose form of fructose is illustrated in the figure, other forms of fructose (e.g., pyranose forms) are equally converted. Thus, no limitations are intended.

[0060] In a preferred embodiment, in the ionic liquid [EMIM]Cl, reaction time and reaction temperature is about 1 h to 3 h at about 80° C., but is not limited thereto. For example, reaction times and reaction temperatures may be selected in the range from about 0.01 minutes at 400° C. to about 12 h at 80° C. Alternatively, reaction times and reaction temperatures may be selected in the range from about 0.01 minutes at 250° C. to about 8 h at 80° C.

[0061] In other ionic liquids, the melting point is lower, allowing for a lower reaction temperature. For example, [EMIM]CH₃SO₃ is a liquid at room temperature. Reaction times and reaction temperatures may be selected at between about 20 h at 20° C. and from about 0.01 minutes at 250° C.

[0062] Continued processing of product furans may lead to formation polymeric products that are easily separated from products of interest.

[0063] FIG. 3 illustrates a reaction process for conversion of glucose to HMF in an exemplary ionic liquid, e.g., ([EMIM]Cl), with CrCl₂ metal halide catalyst added, according to another embodiment of the process of the invention. As illustrated in the figure, in the ionic liquid treated with CrCl₂ metal halide catalyst, conversion of glucose to HMF occurs.

[0064] In a preferred embodiment, a reaction time and a reaction temperature are 3 h at about 100° C. are used, but is not limited thereto. For example, reaction temperatures and reaction times may be selected in the range from 1 minute to about 20 minutes at 150° C. or about 0.01 minutes at 250° C.; or 0.01 minutes at about 400° C.

[0065] In other embodiments, hydrolysis of cellulose to glucose, dehydration of glucose to HMF has been demonstrated. In a preferred embodiment, a reaction time and a reaction temperature of

[0066] In a preferred embodiment, a reaction time and reaction temperature are 0.5 h at about 140° C. is used, but is not limited thereto. For example, reaction temperatures and reaction times may be selected in the range from about 5 minutes and about 200° C.; or about 0.1 minutes at about 250° C.; or about 0.01 minutes at about 400° C.

[0067] FIG. 4 is a histogram that compares conversion results for fructose and glucose to HMF as a function of temperature in an exemplary ionic liquid, [EMIM]Cl, with no added catalyst. As shown in the figure, at sufficiently high temperatures, fructose is converted to HMF, with yields that decrease in the temperature range between about 120° C. and about 80° C. In contrast, glucose does not produce any significant quantity of HMF, even at 180° C. When water is added to the solvent ([EMIM]Cl) at a ratio of about 5:1, glucose is effectively inert.

[0068] A wide range of metal halide catalysts can be added to increase yields of desired end products. Fructose, for example, is rapidly converted to HMF in ionic liquids treated with metal halide catalysts. The catalysts provide efficient conversion. In such reactions, a very low quantity of levulinic acid impurity is formed, typically below about 1% and more particularly below about 0.1%.

[0069] In yet other processes, high yields of HMF are obtained from conversion of glucose in ionic liquids with a metal halide catalyst added. Chromium chlorides (e.g., CrCl₂ and CrCl₃) are uniquely effective catalysts for selective conversion of glucose to HMF, providing yields of greater than or equal to about 70%, described further herein.

[0070] In still yet other embodiments, HMF is produced from conversion of complex biomass materials, including e.g., cellulose in ionic liquid solvents. Yields of approximately 50% are obtained.

[0071] While the exact mechanism for action of metal halide catalysts is unknown in these processes, at catalytic quantities of catalyst (e.g., 0.5% by weight), the ionic liquid solvent is believed to employ an equimolar amount of ionic liquid (e.g., [EMIM]Cl) and the associated metal halide. For purposes of illustration, addition of CrCl₂ in the ionic liquid [EMIM]Cl proceeds as denoted in equation [4]:



Experiments Demonstrating Conversion of Fructose to HMF in Ionic Liquids Treated with Metal Halide Catalysts

[0072] Fructose conversion in ionic liquids treated with and without addition of a catalyst demonstrates broad applicabil-

ity and advantages of the processes of the invention described herein. For example, fructose can be selectively dehydrated to 5-hydroxymethylfurfural (HMF) with low yields of levulinic acid if treated with metal halide catalysts, described further hereafter.

[0073] Catalysts. Metal halide catalysts were tested using a high pressure reactor (e.g., a Symyx® high pressure reactor system equipped with a heated orbital shaker, Symyx Technologies Inc., Santa Clara, Calif., USA), but is not limited thereto. Ionic liquids and selected catalysts and were to reaction vials by mass. Vials were shaken at 700 rpm and heated at 150° C. between about 10 min. and 30 min. (0.5 h) to mix ionic liquid and catalyst.

[0074] Protocol. Fructose was added to reaction vials and introduced to the reactor. The reactor was purged at room temperature with N₂ or air, heated to an operating temperature of 80° C., and shaken at 700 rpm for 3 h, before cooling and venting.

[0075] Sample Analysis. 500 µL of water was added to each reaction vial followed by centrifugation at 3000 rpm for 30 min. Samples were then diluted with water by a factor of two for analysis by high pressure liquid chromatography (HPLC). For initial analyses, samples were injected onto an Aminex Fast Acid column and analyzed by refractive index on an Agilent 1100 series HPLC using a flow rate of 1 mL/min, column temperature of 60° C., and a 0.005M H₂SO₄ mobile phase. Select samples were chosen from the primary HPLC screen for a secondary HPLC analysis on a long column (e.g., an Aminex® model HPX-87H, 7.8 mm×300 mm, 9 µm particle size, column available commercially from Bio-Rad Laboratories, Richmond, Calif., USA) at a flow rate of 0.55 mL/min, a temperature of 60° C., and a 0.005M H₂SO₄ mobile phase. HPLC results were recorded and used to calculate feed conversion percentages, product selectivity, and molar balances. Catalysts were also ranked for effectiveness. Preferred catalysts, for example, exhibited high conversion and good selectivity yields to HMF.

[0076] FIG. 5 is a histogram showing conversion results for fructose in an exemplary ionic liquid treated with various metal halide catalysts, according to different embodiments of the process of the invention. In the figure, metal halide catalysts included: CrCl₂, CrCl₃, FeCl₂, FeCl₃, CuCl, CuCl₂, VCl₃, MoCl₃, PdCl₂, PtCl₂, PtCl₄, RuCl₃, or RhCl₃. As shown, dehydration of fructose to HMF is catalyzed by many metal halide catalysts and mineral acids, e.g., sulfuric acid, (H₂SO₄). Two metal halides were ineffective, i.e., LaCl₃, and MnCl₂. Alkali metal halides (e.g., NaCl, and LiCl) were also ineffective. HMF yields from conversion of fructose ranged from about 63% to about 83% at reaction times of about 3 h at 80° C. Product mixtures were very clean, as evidenced by NMR analysis. For example, yields of levulinic acid and α-angelicalactone were low, typically less than about 0.1%.

Conversion of Glucose to HMF

[0077] Conversion experiments for fructose were repeated using glucose as a feed material. Temperature was raised to 100° C. due to a lower expected reactivity of glucose relative to fructose.

[0078] FIG. 6 is a histogram showing conversion results for glucose in an exemplary ionic liquid, [EMIM]Cl, pretreated with various metal halide catalysts. As shown in the figure, Glucose conversion was high for many of the metal halide catalysts tested, including AlCl₃, FeCl₃, CuCl₂, CuCl, VCl₃, MoCl₃, PtCl₂, PtCl₄, RuCl₃, and RhCl₃. These metal halides

showed a conversion of glucose of 40% or greater. However, HMF yields were low. HMF yields from conversion of glucose were also low using acids (e.g., H₂SO₄) as catalysts. One catalyst, CrCl₂, gave HMF yields of 68-70%, a previously elusive efficiency for conversion of glucose. HMF yields for ionic liquid solvent systems not containing CrCl₂ or CrCl₃ were on the order of 10%. HMF yields could not be accounted for by product instability under reaction conditions. Results indicate that high conversion of glucose is achieved with various metal halide catalysts, in many ionic liquid systems. However, low product yields suggest these metal halides catalyze undesired reaction pathways.

Conversion of Glucose in Ionic Liquid Containing Metal Halide Catalysts CrCl₂, CuCl₂, and FeCl₂

[0079] In additional experiments, conversion of glucose was tested for three specific catalysts, CrCl₂, CuCl₂, and FeCl₂, at 100° C. To ensure uniform catalyst loading, each catalyst-ionic liquid mixture was prepared in a single batch and then added to the reaction vial (500 mg aliquots) containing glucose (50 mg). Following reaction times at selected reaction temperatures, samples were analyzed by HPLC.

[0080] FIG. 7 plots glucose conversion (mol %) in [EMIM]Cl ionic liquid treated with each of three metal halide catalysts, i.e., CrCl₂, CuCl₂, and FeCl₂, respectively, as a function of time. Glucose conversion is highest in ionic liquid containing CrCl₂. Glucose is reactive in ionic liquid containing CuCl₂, but does not provide a high yield of HMF. In ionic liquid containing FeCl₂, glucose shows essentially no reactivity. Results suggest chemistry for conversion of the carbohydrate differs for each of the metal halide catalysts tested. Effectiveness of CrCl₂ catalyst for conversion of glucose to HMF was unexpected.

[0081] FIG. 8 is a histogram showing results for conversion of glucose in two exemplary ionic liquids, [EMIM]Cl and [BMIM]Cl, treated with a preferred metal halide catalyst, CrCl₂. As shown in the figure, conversion of glucose is greater than 90% (mole basis), with yields of HMF of about 68% (in [EMIM]Cl) and 60% (in [BMIM]Cl), respectively.

Conversion of Cellulose

[0082] Conversion of cellulose in an ionic liquid is described hereafter optionally in conjunction with a catalyst. Ionic liquids catalyze all, or a majority, of the chain of necessary reactions, including, e.g., decrystallization, hydrolysis, and/or dehydration, yielding the desired conversion products. For example, hydrolysis of cellulose in ionic liquids that yields simple sugars including HMF with low yields of levulinic acid was an unexpected result. And, use of additional acids is not required for dehydration to occur. Further, conversion of cellulose and other complex carbohydrates in ionic liquids exhibits high selectivity to desired value-added products. Cellulose can also be converted selectively to other products in different ionic liquids systems. Thus, by appropriate selection of ionic liquid, product can be selectively tuned. Conversion in ionic liquids is applicable to conversion of other carbohydrates and polysaccharides including starch. Thus, the disclosure is not intended to be limited to exemplary embodiments and exemplary carbohydrates described herein.

[0083] Following examples provide a further understanding of the invention

Example 1

Conversion of Fructose to HMF in [EMIM]Cl

Metal Halide or Acid Catalyst

[0084] Fructose (99.9%) was supplied by Mallinckrodt. [EMIM]Cl (99%) was supplied by Solvent-Innovation (GmbH, Cologne, GE). Metal halide catalysts were CuCl, CuCl₂, CuBr₂, MoCl₃, FeCl₂, FeCl₃, CrCl₂, CrCl₃, VCl₃, AlCl₃, MnCl₃, PdCl₂, PtCl₂, PtCl₄, RuCl₃, RhCl₃ were supplied by Sigma-Aldrich (St. Louis, Mo., USA) Acid catalyst was H₂SO₄, supplied by Sigma-Aldrich (St. Louis, Mo., USA). 500 mg [EMIM]Cl was loaded into reaction vials. Metal halide catalysts were added to respective vials at a concentration of ~6 mol % with respect to fructose. 2 mg CrCl₂ was added to its reaction vial. Vials were installed into the high pressure reactor, heated at 150° C. and shaken at 700 rpm to mix contents. After cooling, 50 mg fructose was added to each vial and heated at 80° C. for 3 h. After cooling, 2.0 mL of water was added for analysis by HPLC. Results are presented in TABLE 1 (see FIG. 5).

TABLE 1

Conversion of Fructose to HMF, and product yields.				
Example	Feedstock	Catalyst	Feedstock conversion (%)	Product yields (%)*
1.1	Fructose	None	10.92	HMF: 1.36
1.2	Fructose	CuCl	91.25	HMF: 78.81
1.3	Fructose	CuCl ₂	99.54	HMF: 76.02
1.4	Fructose	CuBr ₂	99.59	HMF: 77.48
1.5	Fructose	MoCl ₃	98.67	HMF: 70.88
1.6	Fructose	FeCl ₂	76.40	HMF: 63.15
1.7	Fructose	FeCl ₃	99.80	HMF: 77.08
1.8	Fructose	CrCl ₂	95.32	HMF: 65.26
1.9	Fructose	CrCl ₃	95.41	HMF: 69.28
1.10	Fructose	VCl ₃	100.00	HMF: 77.03
1.11	Fructose	AlCl ₃	99.00	HMF: 76.00
1.12	Fructose	MnCl ₃	10.22	HMF: 5.02
1.13	Fructose	PdCl ₂	92.00	HMF: 77.00
1.14	Fructose	PtCl ₂	99.00	HMF: 83.00
1.15	Fructose	PtCl ₄	99.00	HMF: 80.00
1.16	Fructose	RuCl ₃	98.00	HMF: 79.00
1.17	Fructose	RhCl ₃	99.00	HMF: 83.00
1.18	Fructose	H ₂ SO ₄	99.00	HMF: 80.00

*Yields of levulinic acid and α -angelicalactone were less than 0.1% for all experiments.

Example 2

Conversion of Fructose to HMF in Alternate Ionic Liquids

Metal Halide or Acid Catalyst

[0085] Fructose was processed as in Example 1 in various ionic liquids containing a metal halide or acid catalyst. Ionic liquids were [EMIM]CH₃SO₃ (Solvent-Innovations, GmbH, Cologne, GE); tetrabutylammonium chloride (Fluka-Sigma-Aldrich, Steinheim, GE); tetrabutylphosphonium chloride (Ionic Liquid Technologies, GmbH, Denzlingen, GE); 1,2,4-trimethylpyrazolium methyl sulfate (Fluka-Sigma-Aldrich, Steinheim, GE). [EMIM]CH₃SO₃, tetrabutylphosphonium chloride, and 1,2,4-trimethylpyrazolium methyl sulfate each contained a catalytic quantity of acid. Results are presented in TABLE 2.

TABLE 2

Conversion of Fructose to HMF, and product yields.				
Example	Feedstock	Ionic Liquid (IL) and Catalyst	Feedstock conversion (%)	Product Yields (%)
2.1	Fructose	IL: [EMIM]CH ₃ SO ₃ ; Catalyst: acid	99.6	HMF: 86.5
2.2	Fructose	IL: tetrabutylammonium chloride; Catalyst: VCl ₃	—	HMF: 59.1
2.3	Fructose	IL: tetrabutylphosphonium chloride; Catalyst: acid	—	HMF: 65.2
2.4	Fructose	IL: 1,2,4-trimethylpyrazolium methyl sulfate; Catalyst: acid	—	HMF: 52.1

Example 3

Carbohydrate Reactivity in “as-Received” and Purified Ionic Liquid

[0086] Carbohydrate reactivity was compared in both “as-received” (as purchased) and purified ionic liquid. Fructose was processed as in Example 1 in 99% [EMIM]CH₃SO₃ (Solvent-Innovation, GmbH, Cologne, GE) in both the “as-received” ionic liquid and the ionic liquid purified with basic alumina to remove any contaminants (e.g., methane sulfonic acid). Reaction time and temperature was 3 h at 80° C. Conversion of fructose in the “as-received” ionic liquid was 99.9%; yield of HMF was 83.9%. Conversion of fructose in purified ionic liquid was 0%; yield of HMF was 0%. Results demonstrate that some impurities present in ionic liquids (e.g., as purchased) are sufficient to catalyze reaction of carbohydrates. When purified, the ionic liquid does not exhibit reactivity at the same temperature.

Example 4

Conversion of Fructose to HMF in [EMIM]CH₃SO₃ Acid Catalyst

[0087] Fructose was processed as in Example 1 in (99%) [EMIM]CH₃SO₃ (Solvent-Innovation, GmbH, Cologne, GE) ionic liquid, containing a catalytic quantity of CH₃SO₃. Liquid products were analyzed by HPLC. Conversion of fructose was 99.6%; yield of HMF was 86.5%; yield of levulinic acid yield was 0.5%. Yields of HMF in repeat experiments ranged from 86% to 90%.

Example 5

Conversion of Fructose to HMF in [EMIM]Cl No Metal Halide or Acid Catalyst

[0088] Fructose was processed as in Example 1 in [EMIM]Cl at a reaction temperature of 120° C. for 3 h. Conversion of fructose was 98%; yield of HMF was 73% (see FIG. 4).

Example 6

Conversion of Glucose to HMF in [EMIM]Cl; CrCl₂ Metal Halide Catalyst

[0089] Glucose was processed as in Example 1 at a reaction temperature of 100° C. for 3 h in [EMIM]Cl. Metal halide catalyst was CrCl₂. Results are listed in FIG. 6 and TABLE 3.

Example 7

Conversion of Glucose to HMF in [EMIM]Cl

CrCl₃ Metal Halide Catalyst

[0090] Glucose was processed as in Example 1 at a reaction temperature of 100° C. for 3 h in [EMIM]Cl. Metal halide catalyst was CrCl₃. Results are listed in FIG. 6 and TABLE 3.

Example 8

Conversion of Glucose to HMF in [EMIM]Cl Various Metal Halide and Acid Catalysts

[0091] Glucose was processed as in Example 1 in [EMIM]Cl at a reaction temperature of 100° C. for 3 h. Metal halide catalysts were CuCl, CuCl₂, CuBr₂, MoCl₃, FeCl₂, FeCl₃, CrCl₂, CrCl₃, VCl₃, AlCl₃, MnCl₃, PdCl₂, PtCl₂, PtCl₄, RuCl₃, RhCl₃. Acid catalyst was H₂SO₄. Results are presented in FIG. 6 and TABLE 3.

TABLE 3

Conversion of Glucose to HMF, and product yields.				
Example	Feedstock	Catalyst	Feedstock conversion (%)	Product yields (%)*
6	Glucose	CrCl ₂	94.4	HMF: 68.0
7	Glucose	CrCl ₃	71.5	HMF: 44.3
8.1	Glucose	None	0	HMF: 0
8.2	Glucose	CuCl	0	HMF: 0
8.3	Glucose	CuCl ₂	85.0	HMF: 6.4
8.4	Glucose	CuBr ₂	40.4	HMF: 4.7
8.5	Glucose	MoCl ₃	46.8	HMF: 7.2
8.6	Glucose	FeCl ₂	0	HMF: 0
8.7	Glucose	FeCl ₃	47.8	HMF: 6.4
8.8	Glucose	VCl ₃	61.2	HMF: 8.1
8.9	Glucose	AlCl ₃	97.3	HMF: 10.8
8.10	Glucose	MnCl ₃	0	HMF: 0
8.11	Glucose	PdCl ₂	20.0	HMF: 0.7
8.12	Glucose	PtCl ₂	65.0	HMF: 7.6
8.13	Glucose	PtCl ₄	88.0	HMF: 13.0
8.14	Glucose	RuCl ₃	65.0	HMF: 7.1
8.15	Glucose	RhCl ₃	55.0	HMF: 3.9
8.16	Glucose	H ₂ SO ₄	94.4	HMF: 11.0

*Yields of levulinic acid and α -angelicalactone were less than 0.1% for all experiments.

Example 9

Conversion of Cellulose to HMF in [EMIM]Cl

CrCl₂ Metal Halide Catalyst

[0092] 500 mg [EMIM]Cl, (99.5%) (Solvent-Innovation GmbH, Cologne, Germany) and 0.037 mmol/mL of CrCl₂ metal halide catalyst were added to a reaction vial. The vial was heated to 180° C. to create a homogenous catalyst system. 50 mg of cellulose (Sigma-Aldrich, St. Louis, Mo., USA) was added and mixed at 700 rpm to swell the cellulose. Vial was heated at 180° C. for 1 h. 50 µL of water was added for analysis by HPLC. Yield of HMF was 49.8%.

Example 10

Conversion of Cellulose in [EMIM]Cl

CrCl₃ Metal Halide Catalyst

[0093] Cellulose was processed as in Example 9 in [EMIM]Cl at 140° C. for 0.5 h. Metal halide catalyst was CrCl₃. Products were analyzed by HPLC. Yield of HMF was 50.7%; yield of levulinic acid was 1.4%; yield of formic acid was 2.5%. Results for Examples 9-10 are listed in TABLE 4.

TABLE 4

Conversion of Cellulose to HMF, and product yields.				
Example	Feedstock	Process conditions for hydrolysis and dehydration	Feedstock conversion (%)	Product yields (%)
9	Cellulose	Temp: 180° C., Time: 3 h Catalyst: CrCl ₂	—	HMF: 49.8
10	Cellulose	Temp: 140° C., Time: 0.5 h, Catalyst: CrCl ₃	—	HMF: 50.7 Levulinic acid: 1.4 Formic acid: 2.3

by HPLC. Conversion of sorbitol was 97.2%, yield of 1,4-sorbitan was 51.6%; yield of isosorbide was 20.0%.

Example 12

Conversion of Sorbitol in [OMIM]Cl

CuCl₂ Metal Halide Catalyst

[0095] Sorbitol was processed as in Example 9 in [OMIM]Cl with 50 mg CuCl₂ added as catalyst. Conversion of sorbitol was 95.8%; yield of 1,4-sorbitan was 36.3%; and yield of isosorbide was 37.3%.

Example 13

Conversion of Sorbitol in [EMIM]CH₃SO₃

No Metal Halide Catalyst

[0096] Sorbitol was processed as in Example 9 in [EMIM]CH₃SO₃. Liquid products were analyzed by HPLC. Conversion of sorbitol was 82.4%; yield of 1,4-sorbitan was 63.8%; yield of isosorbide was 1.6%.

Example 14

Conversion of Sorbitol in [EMIM]Cl;

ZnCl₂ Metal Halide Catalyst

[0097] Sorbitol was processed as in Example 9 in [EMIM]Cl with 50 mg ZnCl₂ added as catalyst. Products were analyzed by HPLC. Conversion of sorbitol was 92.1%; yield of 1,4-sorbitan was 76.0%; yield of isosorbide was 3.8%.

[0098] Results of Examples 11-14 are summarized in TABLE 5.

TABLE 4

Conversion of Sorbitol, and product yields.				
Example	Feedstock	Ionic Liquid and Catalyst	Feedstock conversion (%)	Product yields (%)
11	Sorbitol	IL: [OMIM]Cl, Catalyst: None	97.2	1,4-sorbitan: 51.6 Isosorbide: 20.0
12	Sorbitol	IL: [OMIM]Cl, Catalyst: CuCl ₂	95.8	1,4-sorbitan: 36.3 Isosorbide: 37.3
13	Sorbitol	IL: [EMIM]CH ₃ SO ₃ , Catalyst: None	82.4	1,4-sorbitan: 63.8 Isosorbide: 1.6
14	Sorbitol	IL: [EMINA]Cl, Catalyst: ZnCl ₂	92.1	1,4-sorbitan: 76.0 Isosorbide: 3.8

Example 11

Conversion of Sorbitol in [OMIM]Cl

No Metal Halide Catalyst

[0094] 50 mg sorbitol and 500 mg [OMIM]Cl were introduced to a vial. The vial was installed into a high pressure reactor, evacuated, purged with N₂. The vial was shaken at 700 rpm and heated at 150° C. under 25-torr vacuum for 1 h. The vial was cooled and 2.0 mL water was added for analysis

[0099] As demonstrated in Examples 11-14, sorbitol is dehydrated to products including, e.g., isosorbide and 1,4-sorbitan. Yields are selectively tunable by choices of ionic liquid and catalyst.

[0100] While Examples presented herein demonstrate conversion of carbohydrates using a single batch process and reactor, the invention is not limited thereto. Those of skill in the art will appreciate that many reactors and reactor configurations are suitable for use in conjunction with the invention, including, e.g., step-wise and/or serial processing, multistage processing and reactors, continuous flow processing and

reactors, and/or tandem stage processing and reactors. All reactor configurations and processes as will be contemplated and implemented by those of skill in the art in view of the present disclosure are within the scope of the invention.

[0101] While preferred embodiments of the invention have been shown and described herein, many changes and modifications may be made without departing from the invention in its broader aspects. The appended claims are therefore intended to cover all such changes and modifications as fall within the scope of the invention.

We claim:

1. A method for selective conversion of a glucose containing carbohydrate to produce a furan said method comprising the steps of:

mixing said carbohydrate up to a limit of solubility with an ionic liquid; and

heating said carbohydrate in the presence of a catalyst at a reaction temperature and a reaction time sufficient for conversion of same.

2. The method of claim 1, wherein said ionic liquid has a chemical formula 1-R₁-3-R₂-imidazolium chloride, where R₁ and R₂ are alkyl groups of formula (C_xH_{2x+1}) where X=1 to 18.

3. The method of claim 1, wherein said ionic liquid includes a cation of chemical formula 1-R₁-3-R₂-imidazolium where R₁ and R₂ are alkyl groups of formula (C_xH_{2x+1}) where X=1 to 18, and an anion.

4. The method of claim 3, wherein said anion is selected from the group consisting of halides, sulfates, sulfonates, phosphates, acetates, phosphates, triflates, hexafluorophosphates, tetrafluoroborates, hexafluoroborates, and aluminum chloride.

5. The method of claim 3, wherein said anion is selected from the group consisting of methanesulfonate or trifluoromethanesulfonate.

6. The method of claim 1, wherein said ionic liquid is selected from the group consisting of pyridinium salts, phosphonium salts, tetralkylammonium salts, and combinations thereof.

7. The method of claim 1, wherein said reaction temperature is about 100° C. and said reaction time is between about 3 hours and about 8 hours.

8. The method of claim 1, wherein said reaction temperature is about 120° C. and said reaction time is between about 1 hour and about 3 hours.

9. The method of claim 1, wherein said catalyst is an acid.

10. The method of claim 1, wherein said catalyst is a metal halide.

11. The method of claim 1, wherein said metal halide is selected from the group consisting of AlCl₃, CrCl₂, CrCl₃, FeCl₂, FeCl₃, CuCl, CuBr, CuCl₂, CuBr₂, VCl₃, MoCl₃, PdCl₂, PtCl₂, PtCl₄, RuCl₃, RhCl₃, and combinations thereof.

12. The method of claim 1, wherein said reaction temperature is about 80° C. and said reaction time is between about 1 hour and about 4 hours.

13. The method of claim 1, wherein said ionic liquid is 1-ethyl-3-methylimidazolium methanesulfonate and said catalyst is methane sulfonate or its conjugate acid; and wherein said reaction temperature and said reaction time are between about 80° C. for 2 hours and about 30° C. for 12 hours.

14. The method of claim 1, wherein yield of levulinic acid and α-angelicalactone is below about 0.1 percent by weight.

15. The method of claim 1, wherein said catalyst is a chromium halide.

16. The method of claim 1, wherein said furan is furfural.

17. The method of claim 1, wherein said carbohydrate is converted in a batch reactor or a batch reactor system.

18. The method of claim 1, wherein conversion of said carbohydrate is greater than or equal to about 80 percent and said yield of said furan is greater than or equal to about 50 percent on a mole basis.

19. The method of claim 1, wherein said yield of said furan is at least about 35 percent by weight.

20. A method for selective conversion of fructose to produce a furan said method comprising the steps of:

mixing said carbohydrate up to a limit of solubility with an ionic liquid; and

heating said carbohydrate at a reaction temperature and a reaction time sufficient for conversion of same.

21. A method for selective conversion of a carbohydrate to produce a furan said method comprising the steps of:

mixing said carbohydrate up to a limit of solubility with an ionic liquid; and

heating said carbohydrate in the presence of a catalyst at a reaction temperature and a reaction time sufficient for conversion of same.

22. The method of claim 21 wherein said carbohydrate is selected from the group selected from cellulose, sorbitol, glucose and fructose.

* * * * *